

FloorTac™ Plus

Floor Graphic Material

FloorTac™ Plus is designed for attention-grabbing floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes FloorTac™ Plus ideal for short-term indoor advertising where graphics are applied to the floor. When combined with Drytac's Emerytex® or ScuffGuard™ laminating films, FloorTac™ provides a certified slip-resistant finish for the ultimate floor graphic solution.

CAN BE APPLIED TO:

- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

Product Code: PTU

90
micron

White
Monomeric
PVC

■
Matte



(Eco)Solvent
Latex
UV



Grey Acrylic
(Pressure Sensitive)



Widths up to 1370mm



3 MONTHS DURABILITY
INTERIOR

ENGINEERED WITH NO-LIFT TECHNOLOGY



APPLICATIONS

- SCHOOLS
- HOSPITALS
- RETAIL ADVERTISING
- SUPERMARKETS
- RESTAURANTS



DRYTAC
ADHESIVE SCIENCE

www.drytac.com

FloorTac™ Plus

Floor Graphic Material

FloorTac™ Plus is an 90µ (3.5 mil) printable matte white monomeric PVC film with a removable, pressure sensitive grey acrylic adhesive protected by a poly coated Kraft release liner. It is recommended for use with Drytac's Emerytex® and ScuffGuard™ laminating films to provide slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SUITABLE FOR MID TO HEAVY FOOT TRAFFIC AREAS
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

OVERLAMINATE RECOMMENDATIONS
When using FloorTac™ Plus, an overlaminate can be used for maximum life expectancy. Products recommended for use with FloorTac™ Plus are Drytac's Emerytex® and Protac™ Scuff Guard overlaminates

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Monomeric PVC
Adhesive	Grey Acrylic (Pressure Sensitive)
Release Liner	120 gsm Siliconised 1 Side White Coated Paper

PRODUCT CHARACTERISTIC

Film Thickness	3.5 mil (90µ) 4.3 mil (110µ)
Adhesive Layer	0.8 mil (20µ) (110µ)
Film/Adhesive Ratio	3.5:0.8
UV Protection Factor	Not Applicable (unless combined with Emerytex® or ScuffGuard overlaminates)
Outdoor Durability	Not Applicable
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 176°F (-40°C to 80°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com