SpotOn®

SynPaper for PageWide® XL

TOOL FREE APPLICATION

This high quality, ink receptive white synthetic paper was specifically developed for printing with HP PageWide®, but other aqueous and UV inkjet technologies also provide excellent results. SpotOn® SynPaper for PageWide® XL allows for easy, bubble-free application of vibrant graphics. SpotOn® SynPaper for PageWide® XL is a printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive.

- GRAPHICS FOR SEASONAL PROMOTIONSAPPLICATIONS.
- TRADE SHOW EXHIBITIONS.
- IDEAL FOR SHORT-TERM WALL AND WINDOW APPLICATIONS.
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Product Code: SPOP

120 micron White Matte PP — Matte

HP PageWide® XL

Removable DOT Pattern Polyacrylate Adhesive

Width 1016mm

1 YEAR DURABILITY — **INTERIOR**

APPLICATIONS

MOUNT TO BOARDS

WINDOW GRAPHICS

TEMPORARY SALES SIGNAGE

CAD DOCUMENTS

PRESENTATIONS

POP & EVENT SIGNAGE

GROCERY STORE SIGNAGE

ADVERTISEMENTS

DRYTAC®
ADHESIVE SCIENCE

SpotOn®

SynPaper for PageWide® XL

TECHNICAL SPECIFICATION

SpotOn® SynPaper for PageWide® XL is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconised clay coated Kraft release liner. This high quality, ink receptive white synthetic paper was specifically developed for printing with HP PageWide®, but other aqueous and UV inkjet technologies also provide excellent results. SpotOn® SynPaper for PageWide® XL allows for easy, bubble-free application of vibrant graphics.

- GRAPHICS FOR SEASONAL PROMOTIONS APPLICATIONS.
- TRADE SHOW EXHIBITIONS.
- SHORT-TERM WALL AND WINDOW APPLICATIONS.

INSTALLATION RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Matte White PP
Adhesive	Removable Dot Pattern Polyacrylate
Release Liner	90 gsm Siliconised 1 Side Bleached Clay Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4.8 mil (120µ)	5.3 mil (133µ)
Adhesive Layer	0.5 mil (13µ)	
Film/Adhesive Ratio	4.8:0.6	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Application Temperature	>41˚F (5˚C)	
Service Temperature Range	-4˚F to 149˚F (-20˚C to 65˚C)	
Shelf Life	1 year	
Storage Conditions	64˚F to 77˚F (18˚C to 25˚C); 40 - 65% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013